



At the heart of the image

I AM THE NIKON D5600

D5600



Recommended accessories



EN-EL 14a



ME-1 Stereo Microphone



SB-500 Speedlight



SNAPBRIDGE



BUILT-IN BLUETOOTH



BUILT-IN WIFI



NIKKOR



EXPEED 4



TOUCH & VARI-ANGLE SCREEN

I AM SPREADING CREATIVITY

Fire up your creative spirit. Give power to your ideas. Whether it's shadow play when the sun's high, or movies shot from intriguing angles, the new Nikon D5600 is where the magic happens. SnapBridge keeps the camera connected to your smart device so you can share and inspire instantly.

Key features:

- **Move the imagination: Nikon DSLR image quality.** Image quality is everything. The large 24.2 megapixel DX-format sensor, wide ISO range, and your NIKKOR lens combine to deliver stunning images and incredible detail—even in low light.
- **Too good not to share: always connected with SnapBridge.** Connect and inspire as you share your DSLR-quality images in seconds. SnapBridge utilises Bluetooth® low energy technology* to let the D5600 maintain a constant, low-power link with your smartphone or tablet.
- **Catch what you see, the way you see it: vari-angle touchscreen.** Simply flip, tilt, or rotate the large 8.1 cm (3.2 in) vari-angle touchscreen to get a clear view. Tap to focus and shoot.
- **Miss nothing: speed and precision to capture every idea.** When you notice everything, you want a camera that misses nothing. The razor-sharp 39-point autofocus system will lock onto your subject and keep it in focus even in the midst of the action.
- **Movies you'll be proud to share: D-Movie and Time-Lapse Movie.** Record smooth, finely detailed Full HD video clips at frame rates of up to 50p/60p. Transform slow-moving scenes into dramatic high-speed sequences with Time-Lapse Movie. Share easily via SnapBridge.

* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Nikon and its Affiliates is under license.

D5600



At the heart of the image

D5600

TECHNICAL SPECIFICATIONS

Effective pixels	24.2 million
Image sensor	Nikon DX-format CMOS sensor without optical low-pass filter
Viewfinder	Pentamirror type, approx. 95% frame coverage, approx. 0.82× magnification
Monitor	8.1-cm/3.2-in., TFT, approx. 1037k-dot, 170° viewing angle, approx. 100% frame coverage, touch-screen, vari-angle monitor
Touch Fn	Focus point selection, ISO sensitivity (auto sensitivity control [On/Off]), Active D-Lighting setting, HDR, auto bracketing, AF-area mode, viewfinder grid display, aperture setting
Shutter speed	1/4000 to 30 s in steps of 1/3 or 1/2 EV, bulb, time
Continuous shooting	Approx. 5 fps (in 12-bit RAW), approx. 4 fps (14-bit RAW)
ISO sensitivity	ISO 100 to 25600
Autofocus	In viewfinder photography: 39 points (nine cross-type sensors)/in live view photography: contrast-detect AF
Exposure metering	2016-pixel RGB sensor
Built-in flash	Guide number: approx. 12/39 (ISO 100, m/ft, 20°C/68°F)
Scene modes/Effects	16 options, 10 special effects, 20 image-editing functions
Image processing	EXPEED 4 image-processing engine, Picture Control, Active D-Lighting
Movie	• MOV (Video: H.264/audio: LPCM) • 1080: 60p/50p, 1080: 30p/25p/24p, 720: 60p/50p; high quality/normal are selectable • Time-lapse movie
Audio	Built-in stereo microphone, external stereo microphone employed; microphone sensitivity can be set
HDMI	HDMI output supported (HDMI output of 60p/50p movie is unavailable), HDMI connector (Type C) incorporated
Power source	EN-EL14a Rechargeable Li-ion Battery, MH-24 Battery Charger
Dimensions (W x H x D)/Weight	124 × 97 × 70 mm/4.9 × 3.9 × 2.8 in., approx. 415 g/14.7 oz (Based on CIPA Guideline; approx. 465 g/1 lb 0.4 oz with batteries and SD memory card)
Wireless functions	Bluetooth, NFC, Wi-Fi (SnapBridge supported)
Storage media/format	SD memory card (SDHC/SDXC [UHS-I supported]); 12-bit/14-bit RAW, JPEG, RAW+JPEG
Interface	External microphone connector, Micro-USB connector, accessory terminal, HDMI connector (Type C)
Supplied accessories	EN-EL14a Rechargeable Li-ion Battery, MH-24 Battery Charger, AN-DC3 Strap, BF-1B Body Cap, DK-25 Rubber Eyecup



D5600

Nikon will not be held liable for any errors this manual may contain.
The appearance of this product and its specifications are subject to change without notice.

